

HOW TO SPECIFY ABET LAMINATI STRATIFICATO COMPACT GRADE HIGH PRESSURE LAMINATE R605

Section 06067 Plastic and Metal Surfacing Materials

Note: For additional information, contact:

Abet Laminati
1-800-228-22380
us.abetlaminati.com
ca.abetlaminati.com

PART I GENERAL

1.1 PRODUCT DELIVERY AND STORAGE

Contractor shall supply and install ABET LAMINATI Stratificato compact high pressure laminate as shown on drawings and as specified.

Stratificato compact high pressure laminate should always be transported and stored on flat, stable pallets and the panels secured so they do not slip. Store the laminates in a closed place where normal climatic conditions are guaranteed.

1.2 PRECONDITIONING

ABET LAMINATI Stratificato compact laminates should be allowed to acclimate for ten days before fabrication and installation. Optimum conditions are approximately 23 degrees C (73 degrees F) and a relative humidity of 45% to 50%.

PART II PRODUCTS

2.1 STRATIFICATO COMPACT LAMINATE

The decorative compact grade high pressure laminate shall be ABET Laminati Stratificato compact laminate supplied by ABET Inc. as follows:

Laminate Type/Grade	<u>Stratificato Compact Grade High Pressure Laminate</u>
Thickness	_____
Pattern Number	_____
Finish Name	_____
Core Color	_____

PART III EXECUTION

3.1 INSPECTION

All laminate surfaces shall be inspected prior to fabrication to ensure they are sound, clean, and free of surface defects. The protective film, if applied, must be removed simultaneously from both surfaces.

3.2 INSTALLATION

ABET Laminati Stratificato compact laminate cutting, drilling, and fastening procedures must be followed. Material, equipment, and workmanship should conform to industry practices, conditions, procedures and recommendations as specified by ANSI/NEMA LD-3-2000 (Latest Revision), Annex A, Application, Fabrication, and Installation (of High Pressure Decorative Laminates) and "Architectural Woodworking Quality Standards, Guide Specifications and Quality Certification Program" guidelines of the Architectural Woodwork Institute.

SHORT FORM

Laminate shall be Stratificato high pressure compact grade laminate supplied by ABET Inc., Englewood, N. J..

Type: ABET Laminati Stratificato Compact Grade Laminate

Thickness: _____

Surface:
Color Number _____

Finish:
Finish Number _____

Core Color: _____